

AmendmentAmendment to Specification

Please add the following paragraph after the title of the invention as the first sentence of the specification.

BI
cond
C
"This is a continuation of Application No. 08/638,528, filed April 26, 1996,
Patent No. 5,614,948."

Amendment to Claims

Sub D1
BD
cond
1. (Once Amended) A camera comprising:
a sensor configured to capture an image and generate a sensor output signal
representing the captured image;
an amplifier coupled to receive the sensor output signal, wherein the amplifier
is configured to apply multiple gain levels to the sensor output signal; and
a processor coupled to the amplifier, wherein the processor is configured to
provide a control signal to the amplifier to adjust the gain levels applied by the
amplifier, the processor adapted to adjust the gain level of one portion of the
captured image in response to a value of a previous portion of the captured image.

SUB D2
BD
cond
11. (Once amended) An apparatus for capturing an image, comprising a
camera, including:

a sensor configured to capture the image and generate a sensor output signal
representing the captured image;

an amplifier coupled to receive the sensor output signal, wherein the
amplifier has controls to apply multiple gain levels to the sensor output signal; and

B3
concl

a processor coupled to the camera, wherein the processor is configured to receive the sensor output signal, and wherein the processor is configured to provide a control signal to the amplifier to adjust the gain level applied by the amplifier so that the gain level of one portion of the captured image is different than the gain level of another portion of the captured image.

B4 SUB D3
concl

23. (Once amended) An apparatus adapted to process an image, comprising: an amplifier adapted to apply more than one gain level to the image; and a processor coupled to the amplifier, wherein the processor is capable of adjusting the more than one gain level applied by the amplifier in real time.

B5
concl

34. (Once amended) An apparatus capable of processing an image, comprising:

an image capture device coupled to the apparatus and capable of providing the image;

an amplifier coupled to the image capture device, wherein the amplifier is adapted to apply at least two gain levels, each to a different region of the image; and

a processor coupled to the amplifier, wherein the processor is adapted to provide a signal to the amplifier to adjust the at least two gain levels and apply one gain level to a first portion of the image and a second gain level to a second portion of the image.